



Professional battery tester with ultra-precise measurement and intuitive colour display.

## COMPREHENSIVE TESTING FUNCTIONALITY



### 6 and 12 V Battery Test:

- Consists of 4 phases:
- Battery health test
- Cold cranking capacity test (CCA)
- Internal resistance test
- Battery voltage and state of charge test



### 6 and 12 V starter test:

- Start-up voltage test.



### 6 and 12 V alternator test:

- Testing of no-load and under-load voltage, as well as under-load current surge.



### Waveform:

- Controls the waveform of the battery voltage.








## VERSATILE

### Compatible with 3 types of lead-acid battery, ranging from 7 to 240 Ah:

- Sealed batteries VRLA / GEL / AGM FLAT PLATE / AGM SPIRAL
- STANDARD LIQUID batteries
- START / STOP batteries (EFB/AGM)


### Working specifications:

FR	DIN	SAE	JIS	IEC	CA/MCA
				 international standard	marine battery
10 > 2000 A	10 > 1400 A	10 > 2000 A	26A17 > 245H2	10 > 1400 A	10 > 2000 A

## HIGHLY ACCURATE


- Automatic external temperature compensation.
- Dynamic resistance measurement minimises battery discharge and gives a reliable result that is not influenced by:
  - surface charge
  - parasitic load (*lights, various indicators, etc*)
  - contact problems (*terminal oxidisation, loose terminal lugs*)

## INTUITIVE & SAFE



- 3.2-inch colour LCD display.
- Result available in less than 1 second.
- Follow up with a new test straight away.
- Stores the results of the last test performed.
- Reverse polarity protection.

### Interface available in 13 languages



Supplied with carry bag

Disconnectable cables

		TEST			RESULT	TEMPERATURE COMPENSATION				
Battery A	Battery V	CHARGING & STARTING SYSTEM VEHICLE								
6-12 V	7 > 240 Ah	6 V 12 V 24 V	•	min 3 V	1 s	instant	•	10 x 3,8 x 20,5 cm	900 g	2,6 m