

The **POWERDUCTION 10R ONE** is designed to heat, unlock to enable removal of mechanical parts such as worn nuts and bolts in seconds. It is especially recommended in the automotive, agricultural, maintenance and metal construction.

## ERGONOMIC MULTI-APPLICATION TOOL







- Instant heat without flame applied to a specific area, it can be used close to cables, pipes, or other heat sensitive objects avoiding the need to disassemble / remove them.
- Light weight: just 3.5 kg - 1.3 kg for the inductor alone.
- Ergonomic: shoulder strap provided.
- Easy to use: uses a standard 230V single phase supply.
- Quick start: select and install the inductor, connect and go.
- 1200 W output power with high duty cycle.
- Very easy inductor replacement thanks to a knob locking system.















Supplied with 1 inductor



## INDUCTORS (optional)

Spiral wire SIDE		Spiral wire FRONT		Flexible braided wire	Rigid straight wire	Adhesive-removal inductor	Ferrite inductor
							
Ø 18 mm ≤M8	Ø 18 mm ≤M8	80 cm	80 cm	066601	079472		
054806	079977	054813	054868				
Ø 21 mm ≤M10	Ø 21 mm ≤M10						
079953	079984						
Ø 24 mm ≤M12	Ø 24 mm ≤M12						
054790	079991						
Ø 27 mm ≤M14	Ø 27 mm ≤M14						
079960	080003						
Ø 30 mm ≤M16	Ø 30 mm ≤M16						
055469	080010						

											
50/60 Hz	m	A	W	M10	2 mm	Ø8 mm	cm	kg	kg	IP	kW
230 V 1~	2 m	13	1200	1 s	5 s	10 s	21 x 10 x 15	3.5	4.8	IP21	1.5 kW