

The **NOMAD POWER PRO TRUCK 12/24 V** is a lithium-based power pack that combines three functions:

- **Booster for 12 and 24 V vehicles** (motorbikes, quad bikes, cars, SUVs, utility vehicles, light trucks <19 t).
- **Power bank for small electronic devices.**
- **Emergency light/torch.**

## LITHIUM BATTERY BOOSTER

- Equipped with a high-performance lithium battery, the NP PRO TRUCK 12/24 delivers a 1900 A output with an ultra-compact design.
  - The high power output means that all vehicles with a 12V lead-acid battery (liquid, gel, AGM, Start&Stop) can be started in a matter of seconds, even if the vehicle battery is discharged.
- It can also be used to assist in starting vehicles equipped with a 24 V battery.
- ⚠ do not start Lithium LiFePO4 batteries with this booster, as the voltages are not compatible.

## SAFE STARTING

The NOMAD POWER PRO TRUCK 12/24 V protects both the battery and the on-board electronics in the vehicle:

- Anti-spark technology,
- Short-circuit protection,
- Protection against polarity reversal.
- Excessive starting current protection,
- Thermal overload protection for the booster.

## MOBILE ENERGY SOURCE

The capacity of the battery (6 Ah) offers convenience and reliability for keeping your devices charged on the move (mobile phone, tablet, laptop).

- Equipped with:
- 2 x 5 V USB ports (1 A 2.1 A) for charging smartphones, tablets, GPS, etc.
  - 1 cigarette lighter output port 12 V - 10 A, ideal for camping, to supply a 12 V electrical appliance (cool box, fan, etc)

## AUXILIARY LIGHT FUNCTION

Auxiliary light with 3 lighting modes: normal, strobe, SOS.

## COMPACT FORMAT




Very light (2.4 kg) and compact, it can easily be stored in a workshop or recovery vehicle.

## LCD DISPLAY

The NOMAD POWER PRO TRUCK 12/24 V is fitted with an LCD display that shows:

- battery power,
- the charge level of the internal battery,
- the usage of the various inputs and outputs, and the lighting.



	<b>12 V</b>	5 > 140 Ah
	<b>24 V</b>	maximum capacity (requires a minimal charge)
		

## LCD screen



## Supplied with:



USB-C to USB-A charging cable



START		INPUTS / OUTPUTS				POWER BANK	LED	DIMENSIONS				
Lithium		CABLE	INPUT	OUTPUT			✓	✓	3 modes: Light SOS Strobe	24.8 x 24.8 x 9.6	2.4	
Capacity per cell	Full charge			Start	Cranking CC	Peak Battery						5V
6 Ah 155.4 Wh	10 h	USB-C	5V-2A 9V-2A 12V-1.5A	2	5V-1A 5V-2.1A	10 A	—	✓	✓	3 modes: Light SOS Strobe	24.8 x 24.8 x 9.6	2.4